CLIPPO DUO 2x13W LED DIM TO WARM


SPECIFICATIONS		
MOUNTING		CEILING / WALL
POWER	[W]	2x13
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	2x120-1100
LIGHT COLOUR	[K]	1910-3000
CRI		>90
BEAM ANGLE	[°]	33 (default)
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	84

220-240V AC 50/60 Hz POWER SUPPLY [V] [A] LED-DRIVER **INCLUDED** DIMMING PHASE DIM THROUGH-WIRING YES

ALUMINUM MATERIAL **INGRESS PROTECTION** IP20 PROTECTION CLASS 1 1,60 **NET WEIGHT** [kg] **GROSS WEIGHT** [kg] 1,65

COLOUR (HOUSING) WHITE ~RAL9003 COLOUR (HOUSING) BLACK ~RAL9005





*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

REFECTOR 24 / 50 HONEY COMB LOUVER BLACK ANTI GLARE RING GOLD DIMMING DALI





Colours



MOUNTING DIMENSIONS

FIXTURE DIMENSIONS



















DLS LIGHTING

www.dlslighting.com



CLIPPO DUO 2x14W LED


SPECIFICATIONS		
MOUNTING		CEILING / WALL
POWER	[W]	2x14
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	2x1310 / 2x1375
LIGHT COLOUR	[K]	2700 / 3000
CRI		>90
BEAM ANGLE	[°]	32 (default)
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	98

220-240V AC 50/60 Hz POWER SUPPLY [V] [A] LED-DRIVER **INCLUDED** DIMMING PHASE DIM THROUGH-WIRING YES

MATERIAL **ALUMINUM INGRESS PROTECTION** IP20 PROTECTION CLASS 1 1,60 **NET WEIGHT** [kg] **GROSS WEIGHT** [kg] 1,65

COLOUR (HOUSING) WHITE ~RAL9003 BLACK ~RAL9005 COLOUR (HOUSING)





*Luminous flux values are nominal LED data at a operating temperature of 25° C

OPTIONS / OPTIONAL ACCESSORIES

REFECTOR 15 / 48 [°] **LENS** 18 HONEY COMB LOUVER **BLACK** ANTI GLARE RING GOLD DIMMING DALI















white/gold black/black black/gold

MOUNTING DIMENSIONS

FIXTURE DIMENSIONS



















www.dlslighting.com

