



dia poller Design: Sebastian David Büscher



dia poller Design: Sebastian David Büscher

Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar

Installation:
2x Kabeleinführung;
Anschlussklemme
3x 1,5 mm²;
Durchgangsverdrahtung mit
Y-Verbinder in der Leuchte
möglich

Montage:
Bauseitiges Fundament oder
befestigter Untergrund

Material:
Aluminiumguss
pulverbeschichtet
rauchfarbenes Glas

Schutzart:
IP65



Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmbare

installation:
2x cable entry point;
connection terminal
3x 1,5 mm²
possibility of through wiring
with Y-connector
inside luminaire


assembly:
on site foundation or
solid ground

material:
aluminium die-casting
powder-coated
smoke-coloured glass



protection class:
IP65



light direction:



Größe in mm
size in mm

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
 anthracite RAL 7016	91050-AN	6 W/88 lm
 deep black RAL 9005	91050-BL	6 W/88 lm

Zubehör
accessory

Artikel
article

Art.-Nr.
item no.

Y-Verbinder
Y-connector

55312

Erdstück
anchorage unit

55099