



gic Design: Klaus Nolting



gic Design: Klaus Nolting

Lichttechnik:
230V Power LED
2700K
L70/50.000 h

dimmbar

Installation:
2x Kabeleinführung;
Anschlussklemme
3x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Glas satiniert

Schutzart:
IP65

**Dieses Produkt enthält eine
Lichtquelle der Energie-
effizienzklasse F**

Lichtrichtung:



light technology:
230V Power LED
2700K
L70/50.000 h

dimmable

installation:
2x cable entry point;
connection terminal
3x 1,5 mm²

material:
aluminium die-casting
powder-coated
glass satined


protection class:
IP65

**This product contains a light
source of energy efficiency
class F**

light direction:



gic base



**Farbe
colour**

**Art.-Nr.
item no.**


**Systemleistung
system performance**



**anthracite
RAL 7016**

93250-AN

8 W/240 lm



**pure white
RAL 9016**

93250-WH

8 W/240 lm




**deep black
RAL 9005**

93250-BL

8 W/240 lm

Erforderliches Zubehör required accessory

gic cover



**Farbe
colour**

**Art.-Nr.
item no.**


**Material
material**



**anthracite
RAL 7016**

93250-C-AN

**Edelstahl pulverbeschichtet
stainless steel powder-coated**



**pure white
RAL 9016**

93250-C-WH

**Edelstahl pulverbeschichtet
stainless steel powder-coated**



**deep black
RAL 9005**

93250-C-BL

**Edelstahl pulverbeschichtet
stainless steel powder-coated**



brass polished

93250-CB-PO

**Messing poliert
brass polished**



brass brushed

93250-CB-BR

**Messing gebürstet
brass brushed**



**stainless steel
polished**

93250-CS-PO

**Edelstahl poliert
stainless steel polished**



**stainless steel
brushed**

93250-CS-BR

**Edelstahl gebürstet
stainless steel brushed**

**Größe in mm
size in mm**